

Greenmaker Exterior Textured Finishes

- Description**
- This 100% acrylic polymer, Material is engineered to provide a durable, weather-resistant, and decorative finish.
 - Decoplast textured finishes are architectural friendly and will withstand thermal expansion and contraction without delaminating.
 - It is available in 64 standard colors and an infinite number of custom colors.
 - These fade resistant ready-mix textures are very application friendly.
-

- Preparation**
- Greenmaker textured finishes have been formulated to be applied over all Greenmaker base coats as well as conventional stucco brown coat, masonry block, poured precast concrete and plaster.
 - The entire surface should be clean and free of any contaminates.
 - Surface and air temperature should be at a minimum of 45°F during and at least 24 hours after the application.

- Mixing**
- Using a Goldblatt Jiffy Mixer or equivalent, mix the finish until uniform consistency is attained.
 - Based on job site conditions, it may be necessary to add up to 8oz of clean potable water to the mixture.
 - Add the same volume of water to each pail to ensure color and texture consistency.

- Application**
- Greenmaker textured finishes are applied in a single coat using a clean stainless steel trowel.
 - Apply the finish in a uniform thickness slightly thicker than the size of the largest aggregate.
 - Apply the finish with horizontal strokes, keeping the thickness even.
 - The final finish will be achieved with a plastic trowel, applying light pressure in a circular method.
 - This application can be over conventional stucco brown coat, masonry block, poured on concrete and plaster.

Note: It is recommended to apply a coat of Greenmaker Primer prior to finish application.

Cleaning - Clean equipment and containers with water immediately after use.

Cautions

- Protect the material from freezing
- Finishes must be applied at or above 45°F
- Do not apply on damp surfaces or when rain is forecasted
- Consult the manufacturer's Material Safety Data Sheets.

Product Data **Coverage's below are only approximate and may vary with texture and applicator's technique.**

- Freestyle:	varies with texture
- Limestone:	180-200 sq. ft. per pail
- Plaster Smooth:	600-800 sq. ft. per pail
- Fine Sand:	150-170 sq. ft. per pail
- Medium Sand:	100-125 sq. ft. per pail
- Coarse:	80-100 sq. ft. per pail
- Swirl Fine:	160-180 sq. ft. per pail
- Swirl Coarse:	150-170 sq. ft. per pail
- Marmomix:	120-140 sq. ft. per pail

Drying Time

- It is recommended to allow finish application approximately 24 hours to dry. This estimate is based on optimum weather conditions of 70°F, with 55% relative humidity.
- Drying times will vary based on temperature and humidity.

Availability

- Greenmaker textured finishes are available only at authorized Greenmaker distributors.

Warranty

- Consult your nearest Greenmaker Industries professional for details.



697 Oakwood Avenue, West Hartford, CT 06110
voice: 860.761.2830 fax: 860.761.2831
www.decoplast.com